

# AOC®

## e2450Swd



<b>Cabinet Color</b>	Piano-black Glossy Finish
<b>Panel</b>	TFT Active Matrix LCD, WLED Backlight 24" Class Widescreen, 16:9 Aspect Ratio 23.6" Viewable Image Size, Diagonal
<b>Pixel Pitch</b>	0.272 x 0.272mm
<b>Display Area</b>	521.3mm x 293.2mm
<b>Brightness</b>	250 cd/m2 (typ)
<b>Contrast Ratio</b>	20,000,000:1 (dynamic)
<b>Response Time</b>	5ms (typical)
<b>Viewing Angle</b>	Horizontal: 170 Degrees (CR>10) Vertical: 160 Degrees (CR>10)
<b>Scanning Frequency</b>	Horizontal: 30K~83KHz Vertical: 55~75 Hz
<b>Pixel Frequency</b>	165MHz
<b>Maximum Resolution</b>	1920x1080x60Hz
<b>Recommended Resolution</b>	1920x1080@60Hz
<b>Supported Resolutions</b>	640x480@60/67/72/75Hz, 800x600@56/60/72/75Hz, 1024x768@60/70/75Hz, 1280x960@60Hz, 1280x1024@60Hz, 1440x900@60Hz, 1680x1050@60Hz, 1920x1080@60Hz
<b>Color</b>	16.7M
<b>Signal Input</b>	Analog: 0.7Vp-p(standard), 75 OHM, Positive
<b>Digital Input</b>	DVI-D with HDCP*
<b>Connectors</b>	Analog RGB Signal: 15-pin D-sub Male Digital Signal: 24-pin DVI-D
<b>Power Source</b>	Universal 100~240VAC, 50/60Hz
<b>Power Consumption</b>	30Watts (Max)
<b>Plug &amp; Play</b>	DDC/2B, DDC/CI
<b>User Control</b>	-(ECO/DCR), +(4:3/Wide), Source/Auto/Exit, Menu/Enter, Power
<b>OSD Languages</b>	16 Languages including English, French and Spanish
<b>Regulations</b>	cULus, FCC, ROHS, EPEAT Gold
<b>Other Features</b>	User Friendly Graphical OSD Menu, VESA 100mm Wall Mount Compliant*, Kensington Security Slot, Direct-Insert Horizontal Connectors
<b>Dimensions (WxHxD mm)</b>	Monitor: 569.7x413.9x205.1, Carton: 625x437x113
<b>Dimensions (WxHxD inches)</b>	Monitor: 22.4x16.3x8.1, Carton: 24.6x17.2x4.4
<b>Weight</b>	9.8 lbs (4.45 kgs) Net 12.0 lbs (5.45 kgs) Gross
<b>Loading Qty w/pallet</b>	20' = 840 pcs.; 40' Std = 1726 pcs.
<b>UPC Code</b>	685417039388

Note: Specifications are subject to change without notice. \*High-bandwidth Digital Content Protection: Enables viewing of High-Definition contents. \*\*Wall mount arm & bracket not included.

