



Delighting You Always

SOUTH & SOUTHEAST ASIA
REGIONAL HEADQUARTERS

Canon Singapore Pte. Ltd.
1 HarbourFront Avenue
#04-01 Keppel Bay Tower
Singapore 098632
Tel: 65-6799-8888
Fax: 65-6799-8882

www.canon-asia.com

CANON OFFICES

HONG KONG
Canon Hongkong Co., Ltd.
Tel : 852-3191-2388
Fax : 852-2369-3800
www.canon.com.hk

INDIA
Canon India Pvt. Ltd.
Tel : 91-124-4160-000
Fax : 91-124-4160-011
www.canon.co.in

MALAYSIA
Canon Marketing (Malaysia) Sdn. Bhd.
Tel : 603-7844-6000
Fax : 603-7845-0505
www.canon.com.my

PHILIPPINES
Canon Marketing (Philippines), Inc.
Tel : 632-884-9000
Fax : 632-894-4174
www.canon.com.ph

SINGAPORE
Canon Singapore Pte. Ltd.
Tel : 65-6799-8888
Fax : 65-6799-8882
www.canon.com.sg

THAILAND
Canon Marketing (Thailand) Co., Ltd.
Tel : 66-2-3449-999
Fax : 66-2-3449-967/68
www.canon.co.th

VIETNAM
Canon Marketing Vietnam Co., Ltd.
Ho Chi Minh City, Vietnam
Tel : 84-8 38200 466
Fax : 84-8 38200 477
www.canon.com.vn

CANON BUSINESS PARTNERS

BANGLADESH
J.A.N Associates
Tel : 880-2-8611-444
Fax : 880-2-8610-410

BRUNEI
Interhouse Company
Tel: 673-2-6530-01
Fax: 673-2-6530-03

CAMBODIA
i-Click (Cambodia) Pte. Ltd.
Tel : 855-23-966-638
Fax : 855-23-996-639

Royal Cambodia Co., Ltd
Tel : 855-23-4289-55
Fax : 855-23-7229-61

INDONESIA
P.T. Samafitro
Tel : 62-21-3455-521
Fax : 62-21-3844-271

MALDIVES
SIMDI Company (Pvt) Ltd.
Tel : 960-3334-421
Fax : 960-3334-424

MYANMAR
Myanmar Golden Rock
International Co., Ltd.
Tel : 95-1-202092/3/4
Fax : 95-1-202079

NEPAL
International Electronics
Concern (P) Ltd.
Tel : 977-1-4421-991
Fax : 977-1-4421-909

PAKISTAN
MBM International
Tel : 9221-3227-0933
Fax : 9221-3438-6308

SRI LANKA
Metropolitan Communications (Pvt) Ltd.
Tel : 94-11-2437-797
Fax : 94-11-2448-980

imageCLASS
MF4820d



ADVANCED ALL-IN-ONE WITH 2-SIDED PRINTING

MULTI-FUNCTION MONOCHROME LASER PRINTER



COMPACT | QUIET MODE | AUTO-DUPLEX PRINT

ACHIEVING PRINT AND COPY PRODUCTIVITY

With built-in automatic duplex printing, the new imageCLASS MF4820d is designed to deliver productivity and cost-savings without compromising on looks.



The new Vari-Angle Operation Panel affords one-touch simplicity and the best view of the LCD display at all times, while a new Quiet Mode function also comes in handy to keep the device humming along quietly with minimal disturbance to others in the vicinity.

Business *can* be simple

DEALER'S STAMP

0168W736 © 2012 Canon Singapore Pte. Ltd. All rights reserved.
This document is for information purpose only and the contents are subject to change without notice. Product options, name and availability may vary by regions. Nothing in this document should be construed as a warranty. We expressly disclaim any liability or contractual obligations with respect to this document.

FEATURES & PERFORMANCE



VARI-ANGLE OPERATION PANEL

Extend the panel out towards you, or flushed against the front profile for a better viewing experience. A large 5-line LCD display shows more menu options at any time.



A QUIETER WORKING ENVIRONMENT


Pushing the new Quiet Mode key plunges the device into near-stealth operation, reducing engine noise to a bare minimum.



QUICK WARM-UP AND RECOVERY TIMES

With On Demand Fixing technology, users can expect the imageCLASS MF4820d to resume a ready-state in just 2 seconds, ready for the next print or copy job.


Traditional Roller Fixing On-Demand Fixing



Heating entire roller surface results in longer warm-up time and higher power consumption

Heat transferred directly to fixing film reduces warm-up time and saves energy

MULTI-FUNCTION MONOCHROME LASER PRINTER



ONE-TOUCH SOLUTION KEYS

Three task-dedicated Solution Keys on the imageCLASS MF4820d further simplify operations with minimal button-pushing for the most standard of tasks.

// Scan To PC 1 & PC 2

Two user-defined keys that remember your preferred scan settings when scanning to a computer.

// Paper Save Copy

Reduces the number of steps needed to make paper-saving copies, such as 2-on-1 or 4-on-1 copies.

25
Black
ppm

LASER QUALITY PRINTING AND COPYING

With laser quality print and copy speed up to 25ppm/cpm (A4), and First Printout Time at 6 seconds (A4) or less, the imageCLASS MF4820d will complete your multi-page print or copy jobs faster than conventional inkjet systems.

SUPERB PRINT PROCESSING EFFICIENCY

Canon's next-generation UFR II LT page description language enables faster print processing using a unique Load Balancing System between the host PC and device.

INCREDIBLE ENERGY SAVINGS

The imageCLASS MF4820d consumes a mere 1.4W in Standby mode. With features like Auto Duplex printing and copying, and image layout options such 2-on-1 and 4-on-1 copying, you can save the environment while reducing paper costs.

AUTOMATIC TWO-SIDED PRINTING

The imageCLASS MF4820d produces double-sided output automatically via a simple selection on the print driver.

Cartridge
328
GENUINE

MINIMAL DEVICE MAINTENANCE

The Canon All-in-One Toner Cartridge 328 combines the photosensitive drum, toner reservoir, and waste toner container into a compact and precisely-engineered unit, making toner replacements easy and minimizes device maintenance.



QUALITY TONER ENGINEERING

Canon MS-Toner adopts a unique spherical shape to achieve smooth and consistent imaging quality. MS-Toner also improves melting performance, which complements and enhances the On-Demand Fixing process through the use of less heat and pressure.

MF4820d | Specifications

PRINT	
Printing Method	Monochrome Laser
Print Speed (Simplex; A4/LTR)	Up to 25/26ppm (pages per minute)
Print Speed (Duplex; A4/LTR)	Up to 15/16ppm (pages per minute) Up to 7.7/8spm (sheets per minute)
Print Resolution	600 x 600dpi
Print Quality with Image Refinement Technology	1200 (equivalent) x 600dpi
Warm-up Time (From Power On)	12 secs or less
Recovery Time (From Sleep Mode)	Approx. 2.0 secs.
First Printout Time (FPOT)	Approx. 6/5.8 secs (A4/LTR)
Print Language	UFR II LT
Auto Duplex Print	Standard
Available Paper Size for Auto Duplex Print	LTR, LGL, A4 *60 to 105g/m ² recommended
Print Margins	5 mm-top, bottom, left and right (Other sizes than Envelope) 10 mm-top, bottom, left and right (Envelope)
Print Features	Watermark, Page Composer, Toner Saver
COPY	
Copy Speed (Simplex; A4/LTR)	Up to 25/26cpm (copies per minute)
Copy Resolution	600 x 600dpi
First Copy Time (FCOT)	Approx. 9.0/8.7 secs (A4/LTR)
Maximum Number of Copies	Up to 99 copies
Reduce/Enlargement	25 - 400% in 1% increments
Copy Features	Memory Sort, 2 on 1, 4 on 1, ID Card Copy
SCAN	
Scan Resolution	Optical: Up to 600 x 600dpi Driver Enhanced: Up to 9600 x 9600dpi
Color Depth	24-bit
Pull Scan	Yes, USB
Push Scan (Scan to PC) with MF ToolBox	Yes, USB
Scan Features	TWAIN, WIA (Scan Driver Compatibility)
PAPER HANDLING	
Paper Input (Standard)	Plain Paper (60-80g/m ²); 250-sheet Cassette, 1-sheet Multipurpose Tray
Paper Output	100 sheets (face down), 20lb LTR / 68g/m ² A4)
Paper Sizes (Standard Cassette)	A4, B5, A5, LGL, LTR, STMT, EXE, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, FLS, 16K, IndexCard Envelope: COM10, Monarch, C5, DL, Custom (Min. 76.2 x 210mm to Max. 216 x 356 mm)

PAPER HANDLING	
Paper Sizes (Multipurpose Tray)	A4, B5, A5, LGL, LTR, STMT, EXE, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, FLS, 16K, IndexCard Envelope: COM10, Monarch, C5, DL, Custom (Min. 76.2 x 127mm to Max. 216 x 356 mm)
Paper Types	Plain, Heavy, Recycled, Transparency, Label, Envelope
Paper Weight (Standard Cassette)	60 to 163 g/m ²
Paper Weight (Multipurpose Tray)	60 to 163 g/m ²
CONNECTIVITY AND SOFTWARE	
Standard Interface/s (Wired)	USB 2.0 High Speed
Operating System Compatibility	Windows®7 (32/64-bit) Windows®XP (32/64-bit) Windows®Vista (32/64-bit) Mac OS X v10.5.8 or later (*1) Linux (*2)
Software Included	Printer driver, Scanner driver, MF Toolbox, Presto! PageManager
GENERAL SPECIFICATIONS	
Memory	64MB
LCD Display	5-line BW LCD (Vari-Angle Operation Panel)
Dimensions (W x D x H)	390 x 362 x 301mm (Cassette closed) 390 x 439 x 301mm (Cassette opened)
Weight	10.5kg (without cartridge) 11.1kg (with cartridge)
Power Consumption	Maximum: 1320W or less During Operation: Approx. 560W (Average; Copying) During Standby: Approx. 3.5W (Average) During Sleep: Approx. 1.4W (Average)
Noise Levels (*3)	During Operation: Sound Pressure Level (Bystander's position): 51dB in Printing (reference value) Sound Power Level: 6.6B in Printing During Standby: Sound Pressure Level (Bystander's position): Inaudible (reference value) (*4) Sound Power Level: 4.3B or less
Operating Environment	Temperature: 10 to 30°C Humidity: 20% to 80% RH (no condensation)
Power Requirements	AC 220 to 240V: 50/60Hz
Toner Cartridge (*5)	Cartridge 328: 2,100 pages (Bundled cartridge: 1,000 pages)
Monthly Duty Cycle (*6)	Up to 10,000 pages

*1 The latest drivers for Mac OS can be downloaded from www.canon-asia.com when available. *2 Only the print function is supported for Linux. The latest drivers for Linux can be downloaded from www.canon-asia.com when available. *3 Tested in accordance with ISO 7779 and declared per ISO 9296. *4 "Inaudible" means each sound pressure level at bystander's position is less than the absolute criterion value (about background noise) of ISO 7779. *5 Toner cartridge yield in accordance with ISO/IEC 19752. *6 Monthly Duty Cycle value provides a means for comparison of product robustness in relation to other Canon Laser Devices, and does not refer to actual maximum image output per month.