



KV-S1026C DOCUMENT SCANNER

Fast & compact for improved efficiency.

The Panasonic KV-S1026C scanner features a slim and compact body, ideal for business use where space is limited, and offers easy operation with advanced features.

- Fast - High-Speed Scanning at 30 pages per minute

Routine scanning is quick and easy. Scan through mountains of documents and large amounts of daily forms, quickly and effortlessly converting them into digital data.

- Easy to use

Simply press the button and send documents to three pre-registered destinations such as a folder, an email address or a printer.

- Equipped with unique high end features

Features the 'Double Feed Skip' button which enables the scanning of documents such as envelopes and pages with sticky notes. KV-S1026C is able to scan very thin paper from 20g/m² and long paper.

Features

- High-speed scanning up to 30ppm / 60ipm
- 50 Sheet Automatic Document Feeder
- Slim, compact body (W 303 mm x D 177 mm x H 137 mm)
- 3 customisable Single Touch Scan Keys

- Active Double Feed Prevention Roller System
- Simple Touch Free Scanning
- Embossed Card Scanning
- Includes Panasonic Image Capture Plus Software

KV-S1026C PRODUCT GUIDE AND SPECIFICATIONS

Quick

High-Speed Scanning

Routine scanning is quick and easy. Scan through mountains of documents and large amounts of daily forms, quickly and effortlessly converting them into digital data.



Easy

Single Touch Scan

Simply press the button and send documents to three pre-registered destinations.



Reliable

Active Double Feed Prevention

The rotating double feed roller ensures the preceding documents are kept in the feeding area while the top page is fed into the scanner, thus preventing double feeding.



Flatbed Scanner
KV-SS081

Model		KV-S1026C
SCANNER TYPE		Duplex Sheet Feed Scanning
SCANNER TECHNOLOGY		1-Line CIS (Contact Image Sensor)
SCANNING SPEED*1 (A4, Portrait)		Up to 30 ppm / 60 ipm (Binary 200 dpi) Up to 20 ppm / 40 ipm (Colour 200 dpi)
RESOLUTION (Colour and B/W)		Resolution : 100 - 600dpi (1dpi step) Optical : 300/600dpi
AUTOMATIC DETECTION		Ultrasonic Double Feed Detection
IMAGE COMPRESSION		JPEG (Grayscale/Colour)
IMAGE OUTPUT		Binary, Grayscale, Colour, MultiStream (Colour & Binary or Gray & Binary)
BINARY MODE HALFTONE		Dither, Error Diffusion
IMAGE CONTROL		Automatic Binary/Color Distinction, Multi Color Drop Out, Blank Page Removal, Double Exposure, Smooth Background, Automatic Cropping, De-skewing, Dynamic Threshold, White Level From Paper, Image Emphasis (5 steps), Gamma Correction, Automatic Separation, Noise Reduction, Shadow Removal, Mirror Image, Monochrome Reversing, 2-Page Separation and much more.
OTHER FUNCTIONS		Zone OCR (a function of the Image Capture Plus software that adds characters from the document to the output file name), Separation sheet, Single Touch Scan, Skip key
DOCUMENT	SIZE (ADF)	Minimum 48 mm x 70 mm (1.9 in. x 2.8 in.) length Maximum 216 mm x 2,540 mm (8.5 in. x 100 in.) length
	WEIGHT/THICKNESS*2	Single 20 - 209 g/m2 (5.4 lbs. - 55 lbs.) Continuous 20 - 209 g/m2 (5.4 lbs. - 55 lbs.)
AUTOMATIC DOCUMENT FEEDER		Up to 50 sheets (20 lbs., 80 g/m2), 3 hard cards (ISO 7810 ID-1)
SUPPORTED OPERATING SYSTEM		Windows® XP SP3 or later (32-bit), Windows Vista® SP2 or later (32/64-bit), Windows® 7 and Windows® 8 (32/64-bit)
INTERFACE		High-Speed USB 2.0, Up to 480 Mbps transfer rate
POWER REQUIREMENT		AC 100 - 120 V 50/60 Hz, AC 200 - 240 V 50/60 Hz
POWER CONSUMPTION		Scanning mode 17 W or less Idle mode 4.5 W or less Sleep mode 1.6 W or less Power off mode 0.3 W or less
OPERATING ENVIRONMENT		Temperature 10 °C - 35 °C (50 °F - 95 °F) Humidity 20 % RH - 80 % RH
STORAGE ENVIRONMENT		Temperature 0 °C - 40 °C (32 °F - 104 °F) Humidity 10 % RH - 80 % RH
EXTERNAL DIMENSIONS*3 (W x D x H)		303 mm x 177 mm x 137 mm (11.9 in. x 7 in. x 5.4 in.) without Feed tray
WEIGHT*3		2.7 kg (5.9 lbs.)
ACCESSORIES		DVD-ROM : Drivers and Utilities for Windows / Manuals Driver software ISIS / TWAIN Application software Image Capture Plus Safety Guide, Quick Reference Guide, Mixed batch card guide, AC adapter & Power cord, USB cable
OPTIONS	ROLLER EXCHANGE KIT	KV-SS058 (Double-feed prevention roller x 1, Paper feed roller x 1)
	ROLLER CLEANING PAPER	KV-SS03
	FLATBED SCANNER	KV-SS081

*1 The scanning speed differs depending on the host computer, the operating system, the application, the measuring method, the quantity of data in the image, and the paper type. The scanning speed depends on a measuring method of Panasonic.

*2 "Weight in pounds" of paper represents the weight of 500 (432 x 559 mm / 17 x 22 inches) sheets.

*3 Dimensions and weight are approximate

Trademarks and registered trademarks

- ENERGY STAR and the ENERGY STAR mark are registered U.S. marks.

- ISIS® is a registered trademark or trademark of EMC Corporation in the United States and other countries.

- Microsoft®, Windows® and Windows Vista® are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.

- All other brand or product names are the property of their respective holders.

• Design and specifications are subject to change without notice.

This Product is designed to reduce hazardous chemical substances along with the RoHS directive.

Panasonic
ideas for life